



A-FLEX AUTO HD

Properties

- hose for vehicle exhaust gas extraction.
- designed to be in contact with the ground
- crush recoverable construction
- appearance: external smooth printed cover, internal corrugated
- colour: black
- supplied in specific lengths with integrated cuffs at each end
- by means of clamps, collars or other means set by the systems construction



Applications

- vehicle exhaust gas extraction

Construction

- inner tube: heat resistant synthetic rubber
- reinforcement: high strength plies of synthetic cord
- cover: abrasion and heat resistant synthetic rubber

Code - 9AA8T53....

Base Material - EPDM

Operating Temperature - -40 ÷ +120 / peaks +150 °C

Pressure - 0,50 bar

Vacuum - 2,04 ÷ 2,55 mtH₂O

Diameter Range - 76 ÷ 102 mm

Key Feature - Crush recoverable, Reinforced

inner Ø	wall thickness	outer Ø	working pressure	bursting pressure	bending radius	weight	coil length
mm	mm	mm	bar	bar	mm	kg/m	m
76	5,0	81	0,50	2,55	240	2,55	20
102	5,0	107	0,50	2,04	350	3,20	20

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - ott_17 rbd