



Abrasive products

A-FLEX ABR

Properties

- flexible hose for dust extraction, ventilation system, industrial ventilation
- reference standards: ISO 1307

Applications

- for suction and delivery of air, dust, grain, powder etc...

Construction

- inner tube: EPDM rubber, black, smooth
- reinforcement: synthetic textile and steel helix wire
- cover: weather and ozone resistant EPDM rubber, black, corrugated, fabric impression



Code - A8G13....

Base Material - EPDM

Operating Temperature - $-40 \div +70$ °C

Pressure - n.d.

Vacuum - 0,6 bar

Diameter Range - 30 ÷ 102 mm

Key Feature - Anti-static, Spiral hose

inner Ø	wall thickness	working pressure	bursting pressure	vacuum	weight	bending radius	coil length
mm	mm	bar	bar	bar	g/m	mm	m
30	3.5	-	-	0.6	-	120	40
32	3.5	-	-	0.6	-	130	40
35	3.5	-	-	0.6	-	140	40
38	3.5	-	-	0.6	-	150	40
40	3.5	-	-	0.6	-	160	40
45	3.5	-	-	0.6	-	180	40
50	3.5	-	-	0.6	-	200	40
60	3.5	-	-	0.6	-	240	40
70	3.5	-	-	0.6	-	280	40
75	3.5	-	-	0.6	-	300	40
80	3.5	-	-	0.6	-	320	40
90	3.5	-	-	0.6	-	360	40
102	3.5	-	-	0.6	-	400	40

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - 09_21 rbd