



Air/Fumes



Special Products

A-FLEX PP

Properties

- corrugated polypropylene tube
- ridges run orthogonally to the longitudinal axis
- excellent flexibility even at low temperatures
- acids, solvents and mineral oils-proof
- standard color: black.
- other colors available on request
- self-extinguishing properties: norm UL 94, V2 class.

Applications

- dust and shavings suction
- warm and cool air-ducts

Construction

- corrugated polypropylene tube
- profile:
 - A - for Ø from 4,5 up to 35 and for Ø 140
 - B - for Ø from 40 up to 120
 - B and C - for Ø 50



Code - A8P12....

Base Material - PP

Operating Temperature - -20 ÷ +100 °C

Pressure - n.d.

Vacuum - n.d.

Diameter Range - 4,5 ÷ 140 mm

Key Feature - colored on request

Ø nominal	Ø inner	Ø outer	bending radius	weight	coil length
mm	mm	mm	mm	g/m	m
4,5	4,4	7,4	8	12	100
7	6,8	10,0	10	18	100
8,5	8,4	11,4	20	20	100
9	10,4	13,4	20	22	100
11	11,4	15,4	22	26	100
13	14,4	18,1	25	35	100
16	17,0	21,2	30	40	100
20	20,0	24,5	40	50	100
23	23,7	28,2	45	60	50
26	26,5	30,8	50	65	50
28	28,0	32,2	55	70	50
30	30,5	35,0	55	80	50

Ø nominal	Ø inner	Ø outer	bending radius	weight	coil length
mm	mm	mm	mm	g/m	m
35	35,0	40,5	60	95	50
40	40,5	47,5	65	105	50
50	50,5	57,8	80	150	50
60	61,0	68,0	100	200	50
70	70,0	78,0	120	250	50
80	80,0	89,5	130	290	25
90	90,0	99,5	140	350	25
100	100,0	110,5	145	380	25
120	120,0	129,5	180	460	25
140	140,0	155,0	200	600	25

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - ott_17 rbd