



Abrasive products

A-FLEX SAND10

Properties

- delivery NR hose for abrasive materials
- reference standards: ISO 1307, ISO 4649

Applications

- delivery hose, sand and bead blasting application

Construction

- inner tube: NR rubber, black, antistatic, abrasion resistant
- reinforcement: synthetic textile
- cover: black, smooth, antistatic cloth impression NR rubber, abrasion ageing resistant



Code - B8G01....

Base Material - NR

Operating Temperature - -40 ÷ +70 °C

Pressure - 12 bar

Vacuum - n.d.

Diameter Range - 10 ÷ 102 mm

Key Feature - n.d.

inner Ø	outer Ø	working pressure	bursting pressure	vacuum	weight	bending radius	coil length
mm	mm	bar	bar	bar	g/m	mm	m
10	19	12	36	-	321	110	40
13	21	12	36	-	256	117	40
13	25	12	36	-	434	127	40
16	30	12	36	-	583	160	40
19	34	12	36	-	696	190	40
25	40	12	36	-	837	254	40
30	45	12	36	-	987	300	40
32	48	12	36	-	1138	320	40
35	54	12	36	-	1507	350	40
40	60	12	36	-	1803	400	40
50	70	12	36	-	2347	508	40
60	82	12	36	-	2816	600	40
80	105	12	36	-	4247	800	40
90	115	12	36	-	4650	900	20-40
102	126	12	36	-	4940	1000	20-40

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - 05_22