



Foodstuffs
Pharmaceuticals
Cosmetics

A-FOOD NBR

Properties

- very good resistance to high temperatures
- smooth for easy handling with light-coloured, non-marking cover
- excellent resistance of the cover compound to animal and vegetable fats
- contains no phthalate

Applications

- floor wash down and hot-water cleaning in food processing industries, canneries, dairies, slaughterhouses, etc.

Construction

- inner tube: food grade quality, oil resistant NBR, white, smooth
- reinforcement: synthetic textile
- cover: fats and weather resistant NBR/PVC, blue, smooth

Standard/Approval

- EU regulations n° 1935/2004 and 2023/2006
- FDA regulation 21 CFR 177.2600.



Code - F8G15....

Base Material - NBR

Operating Temperature - $-20 \div +95$ °C

Pressure - 10 bar

Vacuum - n.d.

Diameter Range - $13 \div 25$ mm

Key feature - Food suitable

inner Ø	outer Ø	working pressure	bursting pressure	bending radius	weight	coil length
mm	mm	bar	bar	mm	g/m	m
13,0	21,4	10	30	80	0,30	20/40/60/120
16,0	25,0	10	30	95	0,38	20/40/60/120
19,0	28,4	10	30	115	0,48	20/40/60
25,0	35,0	10	30	155	0,62	20/40/60

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications • ott_17 rdb