



Foodstuffs
Pharmaceuticals
Cosmetics



Steam
Hot water

A-FOOD EPDM FDA STEAM

Properties

- highly flexible with a excellent bending radius
- specially adapted to keep round on reels, resistance to kinking
- contains no phthalate

Applications

- cleaning hoses with hot water and steam up to + 160 °C in food processing plants
- suitable for discharge of liquid foodstuff as wine, milk, beer, water, soda

Construction

- inner tube: food grade quality EPDM, white, smooth
- reinforcement: synthetic textile
- cover: weather resistant EPDM, blue, smooth

Standard/Approval

- EU regulations n° 1935/2004 and 2023/2006
- FDA regulation 21 CFR 177.2600



Code - F8G18....

Base Material - EPDM

Operating Temperature - -30 ÷ +160 °C

Pressure - 10 bar

Vacuum - n.d.

Diameter Range - 10 ÷ 25 mm

Key feature - Food suitable

inner Ø	outer Ø	working pressure	bursting pressure	bending radius	weight	coil length
mm	mm	bar	bar	mm	kg/m	m
10	18	10	30	75	0,25	20/40
13	22	10	30	95	0,35	20/40
16	25	10	30	110	0,41	20/40
19	29	10	30	135	0,54	20/40
25	36	10	30	180	0,74	20/40

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications • ott_17 rdb