

Support elements for machines

Series M-600 Adjustable Feet

Properties

- anti-vibration and adjustable feet with a pivoting centre section
- they isolate more than 80% of emitted or received machinery vibrations, preserving all moving parts (gears, shafts, etc.) and avoiding rapid wear
- the elastic part, constructed in NITRILE RUBBER, has good resistance to oils, fats and solvents
- the pivoting mounting bolt assembly with spherical ends fits in the centre of the cap allowing optimum vibration control on damaged or irregular floors

Applications

- support for ovens, cutters, grinders, plastic materials presses, printing machinery, textile machinery etc.



Code - M2A6....

Material - NBR / Metal

Hardness - n.d.

Ref.	Ø A	B	Ø C	D	Load
<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>ISO</i>	<i>mm</i>	<i>kg</i>
M-600	48	20	M10	80	60
M-601	75	28	M12	100	60-125
M-602	100	28	M12	100	125-200
M-603	128	30	M16	170	200-400
M-604	180	36	M16	170	400-700
M-607	180	44	M16	170	700-1400
M-605	226	47	M20	190	1400-2000
M-606	226	60	M20	190	2000-3000
M-608	226	78	M24	215	3000-5000

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications • mag_18 rdb

