



Non-aggressive liquids

A-FLUID RAD 3atm

Properties

- hose for conveying hot water mixed with antifreeze liquids in cooling systems
- reference standards: ISO 1307

Applications

- engine cooling circuit in automotive industry

Construction

- inner tube: EPDM, black, smooth, heat, ageing and weather resistant
- reinforcement: high tensile textile cord
- cover: EPDM, black, smooth with cloth impression, heat, weather resistant



Code - S8G04....

Base Material - EPDM

Operating Temperature - -40 ÷ +100 °C

Pressure - 4 bar

Vacuum - n.d.

Diameter Range - 18 ÷ 70 mm

Key Feature - Reinforced

inner Ø	outer Ø	working pressure	bursting pressure	vacuum	weight	bending radius	coil length
mm	mm	bar	bar	bar	g/m	mm	m
18	24	4	12	-	281	180	40
20	26	4	12	-	307	200	40
22	28	4	12	-	334	220	40
25	32	4	12	-	423	250	40
28	36	4	12	-	573	280	40
30	38	4	12	-	609	300	40
32	40	4	12	-	645	320	40
35	43	4	12	-	699	350	40
38	46	4	12	-	753	380	40
40	48	4	12	-	789	400	40
42	50	4	12	-	825	420	40
45	54	4	12	-	990	450	40
48	57	4	12	-	1095	480	40
50	60	4	12	-	1200	510	40
55	65	4	12	-	1346	550	40
60	70	4	12	-	1493	600	40
65	75	4	12	-	1700	650	40
70	81	4	12	-	1906	700	20

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - 05_22