



Abrasive products



Special Products

A-FLEX PARABENDATO

Properties

- rubber NR hose
- reference standards: ISO 1307

Applications

- coating rollers
- drain without pressure silos and hoppers of abrasive material (sand, gravel, cement, etc.)

Construction

- NR rubber, smooth, insulating, weather and abrasion resistant, fabric impression
- breaking load: 150 kg/cm²
- elongation at break: 500%



Code - V8G01....

Base Material - NR

Operating Temperature - -40 ÷ +70 °C

Pressure - n.d.

Vacuum - n.d.

Diameter Range - 12 ÷ 500 mm

Key Feature - Crush recoverable, Helix free

inner Ø	outer Ø	coil length	weight
mm	mm	m	kg/m
12x20	4	40	0.221
14x24	5	40	0.328
15x25	5	40	0.345
15x35	10	40	0.864
20x30	5	40	0.432
20x40	10	40	1.036
25x35	5	40	0.518
30x40	5	40	0.604
30x50	10	40	1.382
35x45	5	40	0.691
40x50	5	40	0.777
40x54	7	40	1.136
45x55	5	40	0.863
50x60	5	40	0.950
60x70	5	40	1.122

inner Ø	outer Ø	coil length	weight
mm	mm	m	kg/m
80x88	4	12	1,10
90x98	4	12	0,90
102x110	4	12	1,33
152x160	4	12	1,96
168x176	4	12	2,16
193x201	4	9	2,48
200x208	4	12	2,56
220x228	4	6	2,81
254x262	4	12	3,24
273x281	4	10	3,47
305x313	4	12	3,90
323x331	4	6	4,14
400x408	4	7	5,10
500x508	4	6	6,19

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - 09_21 rbd