



Non-aggressive liquids

A-FLUID SBR 10

Properties

- good economical solution
- customized branding on request
- reference standards: ISO 1307

Applications

- water discharge under pressure on industrial and agricultural sites
- all water discharge applications

Construction

- inner tube: SBR, black, smooth
- reinforcement: synthetic yarns
- cover: SBR, black, weather and abrasion resistant smooth



Code - W8G01....

Base Material - SBR

Operating Temperature - $-25 \div +70$ °C

Pressure - 10 bar

Vacuum - n.d.

Diameter Range - $5 \div 25$ mm

Key Feature - Crush recoverable

inner Ø	outer Ø	working pressure	bursting pressure	vacuum	weight	bending radius	coil length
mm	mm	bar	bar	bar	g/m	mm	m
5	10.5	10	30	-	92	50	100
6	12	10	30	-	120	60	100
8	15	10	30	-	173	80	100
9	16	10	30	-	200	90	100
10	16	10	30	-	190	100	100
10	17	10	30	-	204	100	100
12	18	10	30	-	186	120	100
13	19	10	30	-	210	130	100
15	21	10	30	-	236	150	50
16	23	10	30	-	297	160	50
19	26	10	30	-	344	190	50
20	30	10	30	-	540	200	50
22	30	10	30	-	460	220	50
25	33	10	30	-	530	250	50
25	35	10	30	-	700	250	50

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - 05_22